

# Dramatic Fog Effect for Confined Spaces

## **POWER FOG** **- INDUSTRIAL -** **-9D-**



The Ultratec Power Fog Industrial 9D Fog Machine was created to eliminate the challenges of installing fog effects under stages or in close and confined spaces. Designed for ease-of-use, the machine comes standard with 5-pin DMX control, manual remote control or remote show control.

Built with our 1400-watt Heat Exchanger, the machine is rotated 90 degrees in the stainless-steel chassis to stand upright. Rubber feet and plastic glides are already affixed to the machine to offer the utmost stability. The unit is also used extensively in Low Smoke Generators to decrease the size and allow for greater flexibility.

*This fog machine is suitable for situations where continuous output is required over longer durations. Live event environments such as haunted houses, laser tag arenas, and recreational spaces like Escape Rooms are perfect venues for this model. Combined with the Mega Fog Burst attachment, sudden fog effects can be created on cue, adding to its versatility.*



**ultratecfx.com**

**SETTING THE STANDARD IN  
SPECIAL EFFECTS FOR OVER 25 YEARS**

**ultratec**  
special effects®



Terminal Strip Connection for Show Control (Dry Contacts)

Heavy-duty comfortable handle



Built in 5-Pin DMX



Digital DMX Interface

Powder-Coated Stainless Steel Chassis



OPTIONAL Remote Timer/Duration Remote Show Control



MODELS	
CLF-4456	Power Fogger Industrial w/Air Option 110V
CLF-4457	9D Power Fogger Industrial w/Air Option 220V

OUTPUT	
Run Time:	Continuous
Reheat Time:	None
Fluid Consumption:	Burst - 127 cc/ min. - Continuous - 57 cc/ min.
Tech. Benchmark Spec.:	Continuous - 4,000 cfm @ 1 meter visibility; Burst - 8,900 cfm @ 1 meter visibility
Competitive Comparison:	20,000 cfm

SPECIFICATIONS	
Length:	20 in / 51 cm
Width:	10 in / 25 cm
Height:	9 in / 23 cm
Net Weight:	29 lbs / 13 kgs
Power Cord:	6 ft - 1.8 m
Heater Watts:	1,400 Watts
Rating:	110 Volt A.C. 50/60 Hz. 13 Amps.
Regulatory Compliance:	This product has been certified to CSA/UL Standards by QPS Canada Inc.

### WARRANTY

The Power Fog industrial 9D has a five-year warranty due to manufacturer's defect and a lifetime warranty on the heat exchanger provided Ultratec fluids are used.

Visit [www.ultratecfx.com](http://www.ultratecfx.com) to see available accessories, parts and for a complete set of specifications on all models.

**ultratecfx.com**

Canada - USA - Germany

Phone: 519-659-7972 / Toll Free: 800-388-0617 Email: [sales@ultratecfx.com](mailto:sales@ultratecfx.com)

