Best-in-Class Functionality





The Premier Fog Effects Generator is a top choice for all special effect needs. This best-in-class product remains on the cutting edge of the industry and offers great value. Built with our award winning Rapid-Change Technology, it has a heating capacity of 1400 watts and precision temperature controls allowing for continuous flow output.

With its three modes of operations – Stand-Alone, Analog Remote, DMX/ RDM data – the Premier boasts a 25' hand-held timer remote extendable with optional cables. The Premier holds 4L/1 Gallon fog fluid and has a comfortable, large, top grab-handle, a detail often overlooked. This model is ideal for smaller-scale concerts tours, amusement and theme parks, and theatre productions, where continuous use is required for extended period of times.



ultratecfx.com

SETTING THE STANDARD IN SPECIAL EFFECTS FOR OVER 25 YEARS



CLF-4521

CLF-4522

CLF-4523

Fluid Consumption:

Tech. Benchmark Spec.:

Competitive Comparison:

OUTPUT Run Time:

WARRANTY

* Timer Remote Included ** Remote Included

Premier Fog Effects Generator w/Ind'l Optn 110V**

Premier Fog Effects Generator w/Ind'l Optn 220V**

8,900 cfm @ 1 meter visibility

Burst - 127 cc/ min. - Continuous - 57 cc/ min.

Premier Fog Effects Generator 220V*

Continuous

20,000 cfm

warranty on the heat exchanger provided Ultratec fluids are used.

The Premier has a five-year warranty due to manufacturer's defect and a lifetime

Digital DMX Interface

SPECIFICATIONS	
Length:	21 in / 56 cm
Width:	10 in / 25 cm
Height:	9 in / 23 cm
Net Weight:	29 lbs / 13.2 kg
Net Weight (With Fluid)	39 lbs / 17.7 kg
Power Cord:	6 ft – 1.8 m
Heater Watts:	1400 w
Rating:	110 Volt A.C. 50/60 Hz. 12 Amps.

Visit www.ultratecfx.com for a complete set of specifications on all models.