

The World's Most Durable and Dependable Low Fog Machine



When the audience is in place and the lighting is just right, you need your equipment to perform at the highest standards. That's why we've built the Eclipse Low Fog Effects Generator, the world's most durable and dependable low fog machine. Embodied by a one-piece heavy duty polymer plastic casing, the Eclipse is our most rugged LFG ever.

The Eclipse's integrated carry handles combined with its overall smaller size make handling and set-up easy for your crew. A larger, more powerful 600cfm variable speed fan allows the Eclipse to deliver thick, billowing fog. The positive locking 10" quick lock adapter and hose provides ease of use control for pushing low fog, capable of transforming the stage in just moments.

The Eclipse creates low fog effects for live theatre and concert events. Partnered with our Floor Pocket you can push low fog where and when you need it. Additionally, the Eclipse can be partnered with our Fog Curtain to create big reveals, subtle disappearances and fog projection screens heightening the mood of any live performance.



ultratecfx.com

**SETTING THE STANDARD IN
SPECIAL EFFECTS FOR OVER 25 YEARS**

ultratec
special effects®



Smaller Overall Size with Integrated Carry Handles



PowerCon Connections



Powerful 600cfm Variable Speed Fan



Adjust Fan Speed Control



Positive Locking 10" Quick Lock Hose Adapter



One-Piece All Plastic Heavy Duty Design
Solid 1/4" LLDPE Polymer Plastic



Stainless Steel Drain



Operates with high pressure and low pressure liquid CO₂

MODELS

CLF-4000	Eclipse Low Fog Effects Generator 110v
CLF-4004	Eclipse Low Fog Effects Generator 220v
CLF-4052	Eclipse on Cart w/G3000 fog machine 110v (shown)
CLF-4053	Eclipse on Cart w/G3000 fog machine 220v
CLF-4062	Eclipse in Road Case w/G3000 fog machine 110v
CLF-4063	Eclipse in Road Case w/G3000 fog machine 220v
CLF-4072	Eclipse on Cart w/PFI-9D fog machine 110v
CLF-4073	Eclipse on Cart w/PFI-9D fog machine 220v
CLF-4082	Eclipse in Road Case w/PFI-9D fog machine 110v
CLF-4083	Eclipse in Road Case w/PFI-9D fog machine 220v

SPECIFICATIONS

Length:	22.5 in / 57 cm
Width:	19 in / 48 cm
Height:	23 in / 58 cm
Net Weight:	47 lbs / 21 kgs
Power Cord:	5 ft - 1.5 m interconnect cord
Rating:	1 amp AC @ 120 volts @ 50/60 hz
Regulatory Compliance:	This product has been certified to CSA/UL Standards by QPS Canada Inc.

Specifications: Note Specifications are based on the Eclipse Only

The Eclipse ships with standard parts to connect to a CO₂ tank including a 10" High Pressure CO₂ Extension Hose, CGA CO₂ Dewar Tank Fitting 3/8" Kit and CO₂ Adapter CGA 622 Female > CGA 320 Male.

Visit www.ultratecfx.com for a complete set of specifications on all models.

WARRANTY

The Eclipse has a five-year warranty due to manufacturer's defect provided Ultratec fluids are used.

ultratecfx.com

Canada - USA - Germany

Phone: 519-659-7972 / Toll Free: 800-388-0617 Email: sales@ultratecfx.com

ultratec
special effects